





BEADBLASTER™ 96

BALL-MILL HOMOGENIZER FOR PLATES, TUBES AND JARS



-  **Wet, dry or cryogrinding**
-  **Accepts a variety of tubes, plates and jars**
-  **Large, digital touch screen control panel**
-  **See-through safety lid**

The BeadBlaster 96 is an extremely versatile bead mill homogenizer that has applications in a variety of areas, including biological research, environmental testing, and industrial settings. Adapters are available for microplates, microtubes, and 50ml tubes. Stainless steel grinding jars also available.

Wet homogenization, dry grinding and cryogrinding can all be performed with the BeadBlaster 96. The arced motion of the sample holders and powerful motor allow most samples to be processed in 1 minute or less. All parameters are digitally controlled through the large touch screen and 9 programs can be stored in memory.

The safety cover lifts up for easy access to the sample holders and automatically locks during operation. The wrap-around design of the clear acrylic lid allows for visualization during homogenization.



Ordering Information

IPD9600* BeadBlaster 96 Ball Mill Homogenizer

Accessories:

IPD9600-96 Adapter for 96 well plate, set of 2
IPD9600-25S Stainless steel grinding jar, 25ml, set of 2
IPD9600-25G Replacement gasket for above jar, each
IPD9600-50S Stainless steel grinding jar, 50ml set of 2
IPD9600-50G Replacement gasket for above jar, each
IPD9600-50T Adapter for 4x50ml tubes, set of 2
IPD9600-25BS Stainless steel grinding ball, 25mm, each
IPD9600-50BS Stainless steel grinding ball, 10mm, 500g
IPD9600-CK Cryo Kit, contains bucket, gloves, goggles and tongs

*120V. For 220V, add-E to catalog number

Technical Data

| | |
|-------------------------|--------------------------------------|
| Speed/Increments | 180 to 1800rpm/100rpm |
| Ambient operating temp. | 4°C to 40°C |
| Cycle duration | 1 sec to 59 min: 59 sec |
| Pause | 1 sec to 59 min: 59 sec |
| Number of cyclers | 99 |
| Number of programs | 9 |
| Dimensions (WxDxH) | 335 x 500 x 365mm |
| Weight | 64 kg |
| Electrical | 120V, 60Hz or 220V, 50Hz 200W, 6A |
| Warranty | 2 years |