

SKU: 113713000-00805254



light source
 work equipment
 connected load
 Power consumption
 luminous efficacy
 colour temperature
 color rendering index (CRI)
 chromaticity tolerance LED
 System of protection
 class of protection
 technology
 operation
 luminaire body
 lamp cover
 tubular sections

balance of articulation joints
 weight (net)
 mains lead

Fastening
 lens; dimensions
 lens material
 lens; diopters
 special features

LED
 Energy efficiency category A/A+/A++
 electronic plug-in ballast
 100-240 V; 50/60 Hz
 approx. 13 W
 approx. 57 lm/W
 neutral white, approx. 5000 K
 >= 90 (R9>50)
 3 SDCM
 IP20
 II
 multi-stage switchable, continuously dimmable
 multi-function switch
 plastic, untreated, black
 screen, milky, Polyamide
 tubular aluminium section, anodized, aluminium coloured
 anodised
 spring
 approx. 2.5 kg (5.51 lb)
 approx. 3.6 m (11.81 in); mains plug
 BS 1363
 CEE 7/XVI
 NEMA 1-15P
 screw-down flange
 Ø 160 mm (6.29 in)
 glass
 3,5
 light characteristic can be adjusted with a three-way switch,
 arm length 31"



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx
 Emax: 5537 lx
 Emin: 1894 lx

